



Product: [BEL601](#)



DataConnect CAT 6 UTP Cable

Product Description

DataConnect CAT 6 UTP Cable, 4 Pairs, 24 AWG Solid Bare Copper Conductors, U/UTP, PVC Jacket, Indoor

Technical Specifications

Product Overview

Suitable Applications:	Belden DataConnect system is designed to provide standards-compliant cabling solutions for typical Ethernet data applications, include Retail shops, shopping malls & outlets, restaurants, bars/pubs, residential buildings etc., which is suitable for permanent & channel link installation
------------------------	--

Construction Details

Conductor				
Element	Size	Stranding	Material	No. of Pairs
Pair(s)	24 AWG	Solid	BC - Bare Copper	4

Insulation	
Material	PE - Polyethylene
Overall Cable Diameter (Nominal):	5.7 mm (0.22 in)

Electrical Characteristics

Voltage	
UL Voltage Rating	
Max. 72 V DC	

Mechanical Characteristics

Temperature	
Operating	-20°C To +60°C
Bulk Cable Weight:	39 Kg/km

Standards and Compliance

Flammability / Reaction to Fire:	CMX, IEC 60332-1-2
GB Compliance:	GB/T 18380.1
CEC / C(UL) Compliance:	C22.2 No.210
Data Category:	Category 6
TIA/EIA Compliance:	TIA/EIA 568.2-D
ISO/IEC Compliance:	IEC 11801 Class E
Other Standard Compliance(s):	AS/NZS1660.5.6

Product Notes

Notes:	Cabling Filler: Central Spline GB/T Compliance : GB/T 18380.1 Electrical withstand voltage : 1.5kV ac for 2 seconds
--------	---

History

Update and Revision:	Revision Number: 0.33 Revision Date: 04-29-2024
----------------------	---

Part Numbers

Variants

Item #	Color	Putup Type	Length
BEL601 006U305M	Blue	Box	305 m

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.