

WIRELESS CAMERA SYSTEM

The KA-10 wireless camera system is designed for both professional and consumer video camera miking. The wireless feature makes quality recording possible even in tough environment like noise, distance and outdoor.











Shoe Mount Adapter







CM-201B / CM-201F P44

KA-10R / 10T F




Wireless Camera Receiver / Transmitter

The KA-10 system includes KA-10R, KA-10T, KAC50X / KAC150 cable, TG-10CH2, shoe mount adapter, and CM-201 microphone. It is designed for both professional and consumer video camera. The CM-201 provides omni directional pick up pattern to expand the coverage to mike a meeting.


- * Lithium battery can goes for 14 hours which is useful for travel.
- * UHF PLL 16 selectable frequency can render multi system application.

KA-8TH F© CE UHF PLL Handheld Transmitter

* Over 60 meter operation distance virtually meets all kinds of application.












UHF PLL Handheld Transmitter







P.	56

		· ·		· ·	
Model	KA-10R	KA-10T	Model	KA-8TH	Mh-16TH
Internal Microphone	_	Omni-directional Condenser Microphone	Frequency Preparation	PLL Synthesized Control	PLL Synthesized Cont
Frequency Preparation	PLL Synthesized Control	PLL Synthesized Control	Channel number	16	16
Carrier Frequency Range	502~960 MHz	502~960 MHz	Carrier Frequency Range	502~960 MHz	502~960 MHz
RF Outputs	_	10mW	RF Outputs	10mW	10mW
Stability	_	±10kHz	Stability	±10kHz	±10KHz
Frequency Deviation	_	±48kHz	Frequency Deviation	±48kHz	±48KHz
LED Display	Channel	Channel	LED Display	Channel	Channel
Controls	Power On/Off,	Power On/Off,	Controls	Power On/Off,	Power On/Off,
	Channel selection,	Channel selection,		Channel Up/Down,	Channel Up/Down,
	Volume control	Volume control		Mute	Mute
Spurious Emissions	_	<-50 dBC	Spurious Emissions	<-50 dBC	<-50 dBC
Audio Frequency Response	40~18,000 Hz	40~18,000 Hz	Audio Frequency Response	40~16,500 Hz	50~16,000 Hz
Output connector	1/8" Dummy stereo Phone Jack	_	Battery	UM3, AA 1.5V*2	UM3, AA 1.5V*2
Microphone input connector	· —	1/8" Mono Phone Jack			
Battery life	14 hours typical	14 hours typical			
Battery	Lithium cell (3.7V, 1300mAh)	Lithium cell (3.7V, 1300mAh)			
Dimension(mm)	54mm(W)* 17mm(D)* 99mm(H)	54mm(W)* 17mm(D)* 99mm(H)			