











Frequency Preparation PLL Synthesized Control Carrier Frequency Range 494MHz~870MHz Stability ±0.005%

Frequency Deviation ±48kHz LED Display Channel

Controls Power On/Off, Channel selection

Volume control

Spurious Emissions <-50 dBC Audio Frequency Response 40Hz~18kHz

Output connector 1/8" Mono Phone Jack, Compatible with stereo plug

Battery life 14 hours typical Battery Lithium cell

Dimension(mm) 54mm(W)\* 17mm(D)\* 99mm(H)

Internal Microphone Cardioid Condenser Microphone Frequency Preparation PLL Synthesized Control

Carrier Frequency Range 494MHz~870MHz RF Outputs 10mW

Stability ±0.005% Frequency Deviation ±48kHz LED Display Channel

Controls Power On/Off, Channel selection

Spurious Emissions <-50 dBC Audio Frequency Response 40Hz~18kHz

**o**∸⊚ •

TG-10R

TG-10T

Microphone input connector 1/8" Stereo Phone Jack

Battery life Operation Time 14 hours typical Battery Lithium cell

Dimension(mm) 54mm(W)\* 17mm(D)\* 99mm(H)






Single High Definition Earphone 2008 NEW







TG-10T

Wireless Tour Guide Transmitter 2008 NEW

Number of charging slot 10 (receiver or transmitter) Power requirement 100~240V AC

Switching power supply

Indicator lights LED green Charging LED off Charging completed

Dimensions(mm) 283.43mm(W)\* 160.43 mm(D)\* 61.84mm(H)



2008 NEW UHF PLL Stationary Transmitter



TG-10CH

10-Slot Charger Compartment 2008 NEW