



**CM-802F**  
Single Ear-hook Omni-directional Microphone



**TG-10T**  
Wireless Tour Guide Transmitter



**TG-10R**  
Wireless Tour Guide Receiver



**WM-10TG**  
Single High Definition Earphone



This tour must be different,

# TG-10

WIRELESS TOUR GUIDE SYSTEM

would be that difference.



**TG-10CH2**  
Dual-Slot Charger

**TG-10CH36**  
36-Slot Charger

Model.....	TG-10T
Internal Microphone.....	Cardioid Condenser Microphone
Frequency Preparation.....	PLL Synthesized Control
Carrier Frequency Range.....	502MHz~960MHz
RF Outputs.....	10mW
Stability.....	±0.005%
Frequency Deviation.....	±48kHz
LED Display.....	Channel
Controls.....	Power On/Off, Channel selection Volume control
Spurious Emissions.....	<-50 dBc
Audio Frequency Response	40Hz~18kHz
Microphone input connector	1/8" Mono Phone Jack
Battery life.....	14 hours typical
Battery.....	Lithium cell (3.7V, 1300mAh)
Dimension(mm).....	54mm(W)* 17mm(D)* 99mm(H)

Model.....	CM-802F
Connector.....	3.5 mono plug
Frequency Response	50 ~ 18,000Hz
Polar Pattern.....	Omni-directional
Sensitivity (at 1KHz)	-64±3 dB* (0.63mV)*0dB =1V/μbar,1KHz
Impedance.....	Rated impedance 2.2kΩ
Max. SPL for 1% THD	130dB

Model.....	WM-10TG
Drive Unit.....	Super thin dynamic driver with neodymium magnet
Frequency Response	90~15,000 Hz
Impedance.....	32Ω
Sensitivity(at 1 kHz)..	126 dB/mW
Max. Input power.....	0.2W
Input Connector.....	Gold-plated Ø3.5 dummy stereo phone plug

Model.....	TG-10R
Frequency Preparation.....	PLL Synthesized Control
Carrier Frequency Range.....	502MHz~960MHz
LED Display.....	Channel
Controls.....	Power On/Off, Channel selection Volume control
Audio Frequency Response	40Hz~18kHz
Output connector.....	1/8" Dummy stereo Phone Jack
Battery life.....	14 hours typical
Battery.....	Lithium cell (3.7V, 1300mAh)
Dimension(mm).....	54mm(W)* 17mm(D)* 99mm(H)

Number of charging slot	TG-10CH36 : 36 (receiver or transmitter) TG-10CH2 : 2 (receiver or transmitter)
Power requirement.....	TG-10CH36 : Input : AC 100V~240V, 1.2A max switching power supply Output : DC 15V, 6A
LED Indicator.....	TG-10CH2 : 12~18VDC, 600mA Power Connected: Flash Green Charging: Green Full Charged: Turn off
Dimensions(mm).....	TG-10CH36 : 561mm(W)* 399.77mm(D)* 230mm(H) TG-10CH2 : 85mm(W)* 75mm(D)* 41mm(H)